



PRODUCT SUPPORT.....SERVICE NEWS

| | | |
|---------------------------------------|--------------------------------|---------------------------------|
| BULLETIN NO.: 2005-008 | DATE: December 15, 2005 | PAGE: 1 of 1 |
| TITLE: Change of Axle Gear Oil | | RELEASE: Dealer/Customer |
| SECTION: Axle | | MODEL: 50/60ZIV/ZIV-2/ZV |

GENERAL:

The purpose of this document is to announce an alternative axle oil selection for models 50/60ZV, depending upon temperature related to the machine application.

DETAIL:

Please refer to the table provided below.

| Model | Class or Type of Axle Oil | | |
|-------------------|--------------------------------------|--------------------------------------|--|
| | Current Oil | Alternative Oil | Ambient Working Temperature |
| 50/60ZIV/ZIV-2/ZV | Mobil TRANS HD-30 Valvoline DT-30 | Mobil TRANS HD-30 Valvoline DT-30 | Between -13 ~ +95 degrees Fahrenheit (Between -25 ~ +35 degrees Centigrade) |
| | | Mobil TRANS HD-50 Valvoline DT-50 | When over +14 degrees Fahrenheit (When over - 10 degrees Centigrade) |

In each case, remember that it is necessary to use brake friction modifier when replacing axle oil.

Refer to Service News 96-001C for further information.